

**PRODUCT DESCRIPTION**

The MX456 Series corridor wraparound features economy and energy efficient performance. This luminaire utilizes a low brightness, extruded opal lens for dependable performance and good looks. This cost effective LED utility wrap fixture is a commercial ceiling fixture that provides high uniformity, excellent efficiency and reduced glare. Use in a wide variety of applications such as open offices, private offices, conference rooms, reception areas, retail, hallways, industrial assembly, retail open areas and educational facilities. It is also an ideal complimentary wraparound luminaire for diverse applications requiring economical general lighting.

**FEATURES:**

- Surge protector
- White painted parts are treated with a five-stage phosphate bonding process and finished with high reflectance baked enamel
- Low profile design optimizes shipping, storage, and handling
- Wire guard is secured continuously along luminaire sides
- Shallow depth provides sleek, low-profile appearance
- Performance engineered optical lens assembly delivers unique beam angles and reduces glare.
- High quality LED Chips provide high efficiency, heat dissipation, stability, and lumen maintenance
- Driver disconnect provided where required to comply with US and Canadian codes
- May be surface or pendant (cable, hanging chain or stem kits) mounted
- Class II driver, with 0-10V or Triac dimming

**APPLICATIONS:**

- Closets/Storage rooms/Offices
- Conference rooms/Retail
- Reception areas/Hallways
- Education facilities
- Parking Garages



OPTIONS:	Order Code
AC347-480V High Voltage	347V
Occupancy Sensor	OS
Daylight Harvesting	DH
Emergency Backup	EM
CCT 3000K,4000K,5000K	30/40/50
Suspension Chain	SC
Clear Lens	CL



**ORDERING: (KK=CCT, can be 30,35,40,45,50,55)(The lumens are tested with frosted lens)**

Item	Watts	Efficacy	Lumens	CRI	PF	Voltage	Dimension(L*W*H):Inch		
MX456ALM02514BKKW	25W	120lm/w	3,250lm	>80	>0.95	120-277V	50 2/8	2 7/8	3 5/8
MX456ALM04014BKKW	40W	120lm/w	4,800lm	>80	>0.95	120-277V	50 2/8	2 7/8	3 5/8
MX456ALM04024BKKW	40W	120lm/w	4,800lm	>80	>0.95	120-277V	46 5/8	4 6/8	3 5/8
MX456ALM05024BKKW	50W	120lm/w	6,500lm	>80	>0.95	120-277V	46 5/8	4 6/8	3 5/8

\*Please contact your Brandon representative to order products that don't have order codes listed here or any info required Specification and dimension subject to change without notice.