

PRODUCT DESCRIPTION

The MX456 Series corridor wraparound features economy and energy efficient performance. This luminaire utilizes a low brightness, extruded opal lens for dependable performance and good looks. This cost effective LED utility wrap fixture is a commercial ceiling fixture that provides high uniformity, excellent efficiency and reduced glare. Use in a wide variety of applications such as open offices, private offices, conference rooms, reception areas, retail, hallways, industrial assembly, retail open areas and educational facilities. It is also an ideal complimentary wraparound luminaire for diverse applications requiring economical general lighting.

FEATURES:

- Surge protector
- White painted parts are treated with a five-stage phosphate bonding process and finished with high reflectance baked enamel
- Low profile design optimizes shipping, storage, and handling
- Diffuser is secured continuously along luminaire sides
- Shallow depth provides sleek, low-profile appearance
- Diffusion wrap-around lens for smooth light distribution
- Performance engineered optical lens assembly delivers unique beam angles and reduces glare.
- High quality LED Chips provide high efficiency, heat dissipation, stability, and lumen maintenance
- Driver disconnect provided where required to comply with US and Canadian codes
- May be surface or pendant (cable, hanging chain or stem kits) mounted
- Class II driver, with 0-10V or Triac dimming

APPLICATIONS:

- Closets/Storage rooms/Offices
- Conference rooms/Retail
- Reception areas/Hallways
- Education facilities
- Parking Garages



| OPTIONS: | Order Code |
|-------------------------|------------|
| AC347-480V High Voltage | 347V |
| Occupancy Sensor | OS |
| Daylight Harvesting | DH |
| Emergency Backup | EM |
| CCT 3000K, 4000K, 5000K | 30/40/50 |
| Suspension Chain | SC |
| Clear Lens | CL |



ORDERING: (KK=CCT, can be 30,35,40,45,50,55)(The lumens are tested with frosted lens)

| Item | Watts | Efficacy | Lumens | CRI | PF | Voltage | Dimension(L*W*H):Inch | | |
|-------------------|-------|----------|--------|-----|-------|----------|-----------------------|-------|---|
| MX456FLM02514BKKW | 25W | 120lm/w | 3000lm | >80 | >0.95 | 120-277V | 47 2/8 | 2 7/8 | 2 |

*Please contact your Brandon representative to order products that don't have order codes listed here or any info required Specification and dimension subject to change without notice.