

LED Smiling Wraparound

PRODUCT DESCRIPTION

The MX464 Series corridor wraparound features economy and energy efficient performance. This luminaire utilizes a low brightness, extruded PC lens for dependable performance and good looks. This cost effective LED utility wrap fixture is a commercial ceiling fixture that provides high uniformity, excellent efficiency and reduced glare. Use in a wide variety of applications such as open offices, private offices, conference rooms, reception areas, retail, hallways, industrial assembly, retail open areas and educational facilities. It is also an ideal complimentary wraparound luminaire for diverse applications requiring economical general lighting.

FEATURES:

- Surge protector
- White painted parts are treated with a five-stage phosphate bonding process and finished with high reflectance baked enamel
- Low profile design optimizes shipping, storage, and handling
- Diffuser is secured continuously along luminaire sides
- Polycarbonate lens, high flame retardant point
- Tool-less design driver cover snap into housing for easy installation
- Performance engineered optical lens assembly delivers unique beam angles and reduces glare.
- High quality LED Chips provide high efficiency, heat dissipation, stability, and lumen maintenance
- Driver disconnect provided where required to comply with US and Canadian codes
- May be surface or pendant (cable, hanging chain or stem kits) mounted
- Class II driver, with 0-10V or Triac dimming

APPLICATIONS:

- Closets/Storage rooms/Offices
- Conference rooms/Retail
- Reception areas/Hallways
- Education facilities
- Parking Garages



OPTIONS:	Order Code
AC347-480V High Voltage	347V
Occupancy Sensor	OS
Daylight Harvesting	DH
Emergency Backup	EM
CCT 3000K, 4000K, 5000K	30/40/50
Suspension Chain	SC
Continuous Row Joiner	JO
PC Clear/Opal lens	CL/OL



ORDERING: (KK=CCT, can be 30,35,40,45,50,55)

Item	Watts	Efficacy	Lumens	CRI	PF	Voltage	Dimension (L*W*H): Inch		
MX464DLM02512BKKW	25W	120lm/w	3,000lm	>82	>0.95	120-277V	24 5/8	7 2/8	3 4/8
MX464DLM04014BKKW	40W	120lm/w	4,800lm	>82	>0.95	120-277V	45 6/8	7 2/8	3 4/8

*Please contact your Brandon representative to order products that don't have order codes listed here or any info required. Specification and dimension subject to change without notice.