

PRODUCT DESCRIPTION

MX482-LD series is an energy-efficient harsh environment LED vaportight series designed to operate in commercial, institutional, and industrial applications that require a watertight seal. Tight fixture line features four foot and two foot products for replacement and new construction, providing equivalent lumen packages to current fluorescent solutions with significantly higher efficacy and reduced cost of ownership. The IP65-rated LED Vapor tight linear fixtures are designed to replace fluorescent strip fixtures and can be used in parking garage, corporate campus, education facility, storage facility, car washes, tunnels and stairwell lighting.

FEATURES:

- Surge protector
- White painted parts are treated with a five-stage phosphate bonding process and finished with high reflectance baked enamel
- Low profile design optimizes shipping, storage, and handling
- Diffuser is secured continuously along luminaire sides
- Polycarbonate lens, UV resistant
- Tool-less design driver cover snap into housing for easy installation
- Performance engineered optical lens assembly delivers unique beam angles and reduces glare.
- High quality LED Chips provide high efficiency, heat dissipation, stability, and lumen maintenance
- Driver disconnect provided where required to comply with US and Canadian codes
- May be surface or pendant (cable, hanging chain or stem kits) mounted
- Class II driver, with 0-10V or Triac dimming

APPLICATIONS:

- Car Washes/Food processing
- Gas Station/Laboratories
- Industrial Facilities
- Refrigeration/Freezers
- Parking Garage/Utility
- Warehouse/Supermarket



OPTIONS:

Order Code

AC347-480V High Voltage	347V
Occupancy Sensor	OS
Daylight Harvesting	DH
Emergency Backup	EM
CCT 3000K, 4000K, 5000K	30/40/50
Suspension Chain	SC
PC Clear Lens	CL
Stainless Steel Lens Clips	SS-LC



ORDERING: (KK=CCT, can be 30,35,40,45,50,55)(The lumens are tested with frosted lens)

Item	Watts	Efficacy	Lumens	CRI	PF	Voltage	Dimension(L*W*H):Inch		
MX482DLM04014BKKW	40W	130lm/w	5200lm	>80	>0.95	120-277V	49 2/8	4 5/8	3
MX482DLM05014BKKW	50W	130lm/w	3250lm	>80	>0.95	120-277V	25 2/8	4 5/8	3

*Please contact your Brandon representative to order products that don't have order codes listed here or any info required. Specification and dimension subject to change without notice.