

**PRODUCT DESCRIPTION**

Brandon MX898F Series LED High bay is a compact and economical luminaire utilizing the latest in LED technology, offers exceptional lighting in low to high ceiling applications and delivers the best luminous performance. Employing a 0-10V dimming driver, this fixture will work with occupancy sensors and emergency kits for energy saving. Various color temperature, lumen outputs and accessories for distribution, lens and installation make it perfect for industrial, commercial, manufacturing, warehousing, gymnasium and other applications with mounting heights ranging from 10' to 40'.

**FEATURES:**

- Surge protector
- Low profile design optimizes shipping, storage, and handling
- Individual, pure aluminum heat sinks offers heat transmission faster than die cast steel.
- Performance engineered optical lens assembly delivers unique beam angles and reduces glare.
- High quality LED Chips provide high efficiency, heat dissipation, stability, and lumen maintenance
- Polycarbonate lens (option), high flame retardant point
- Driver disconnect provided where required to comply with US and Canadian codes
- May be cable, chain, or pendant mounted
- End holes to attach V bracket for chain or cable hanging.
- Dual universal 0-10V driver for continuous dimming

**APPLICATIONS:**

- Warehouse/Manufacturing plants
- Distribution centers/Industrial
- Commercial/Grocery Stores
- Gymnasiums/Cold Storage



OPTIONS:	Order Code
AC347-480V High Voltage	347V
Occupancy Sensor	OS
Daylight Harvesting	DH
Emergency Backup	EM
CCT 3000K, 4000K, 5000K	30/40/50
Suspension Chain	SC
Continuous Row Joiner	JO
PC Clear/Opal lens	CL/OL



**ORDERING:**

Item	Watts	Efficacy	Lumens	CRI	PF	Voltage	Dimension(L*W*H):Inch		
MX898X-LD60W-DD-2'	60W	125lm/w	7,500lm	>80	>0.95	120-277V	23 6/8	12 4/8	2 5/8
MX898X-LD120W-DD-2'	120W	125lm/w	15,000lm	>80	>0.95	120-277V	23 6/8	16	2 5/8
MX898X-LD120W-DD-4'	120W	125lm/w	15,000lm	>80	>0.95	120-277V	46 1/8	9	2 5/8
MX898X-LD180W-DD-4'	180W	125lm/w	22,500lm	>80	>0.95	120-277V	46 1/8	12 4/8	2 5/8
MX898X-LD240W-DD-4'	240W	125lm/w	30,000lm	>80	>0.95	120-277V	46 1/8	16	2 5/8

\*Please contact your Brandon representative to order products that don't have order codes listed here or any info required Specification and dimension subject to change without notice.