

PRODUCT DESCRIPTION


Brandon MX811-LD series architectural linear LED suspension lighting fixtures bring clean lines and clear light to commercial LED or residential lighting interiors. Our sleek, stylish fixtures are highly effective and efficient lighting solutions for hotels, offices, retail outlets, restaurants, and more. Our Linear Lights are a stylish alternative to downlights. Linear lights can create a functional yet relaxing atmosphere and provide an even wash of light within a space. Our Linear Lighting can be customised to your desired length, look & colour temperature and can either be suspended, surface mounted or recessed to suit your needs. Linear lights are available to be dimmed and the colour temperature can be interchangeable to allow for maximum functionality.

FEATURES:


- Surge protector
- White painted parts are treated with a five-stage phosphate bonding process and finished with high reflectance baked enamel
- Low profile design optimizes shipping, storage, and handling
- Diffuser is secured continuously along luminaire sides
- Shallow depth provides sleek, low-profile appearance
- Performance engineered optical lens assembly delivers unique beam angles and reduces glare.
- High quality LED Chips provide high efficiency, heat dissipation, stability, and lumen maintenance
- Driver disconnect provided where required to comply with US and Canadian codes
- May be surface or pendant (cable, hanging chain or stem kits) mounted
- Class II driver, with 0-10V or Triac dimming

APPLICATIONS:

- Closets/Storage rooms/Offices
- Conference rooms/Retail
- Reception areas/Hallways
- Education facilities
- Parking Garages



OPTIONS:	Order Code
AC347-480V High Voltage	347V
Occupancy Sensor	OS
Daylight Harvesting	DH
Emergency Backup	EM
CCT 3000K,4000K,5000K	30/40/50
Suspension Chain	SC
Clear Lens	CL
Recessed Mounting Kits	RMK



ORDERING: (KK=CCT, can be 30,35,40,45,50,55)(The lumens are tested with frosted lens)

Item	Watts	Efficacy	Lumens	CRI	PF	Voltage	Dimension(L*W*H):Inch		
MX811ELM02512BKKW	25W	125lm/w	3,125lm	>80	>0.95	120-277V	23 7/8	2 6/8	3 1/8
 MX811ELM02514BKKW	25W	125lm/w	3,125lm	>80	>0.95	120-277V	46 2/8	2 6/8	3 1/8
 MX811ELM04014BKKW	40W	125lm/w	5,000lm	>80	>0.95	120-277V	46 2/8	2 6/8	3 1/8
 MX811ELM08018BKKW	80W	125lm/w	10,000lm	>80	>0.95	120-277V	91 1/8	2 6/8	3 1/8

*Please contact your Brandon representative to order products that don't have order codes listed here or any info required Specification and dimension subject to change without notice.