

PRODUCT DESCRIPTION

The MX456 Series corridor wraparound features economy and energy efficient performance. This luminaire utilizes a low brightness, extruded PMMA lens for dependable performance and good looks. This cost effective LED utility wrap fixture is a commercial ceiling fixture that provides high uniformity, excellent efficiency and reduced glare. Use in a wide variety of applications such as open offices, private offices, conference rooms, reception areas, retail, hallways, industrial assembly, retail open areas and educational facilities. It is also an ideal complimentary wraparound luminaire for diverse applications requiring economical general lighting.

FEATURES:

- Surge protector.
- White painted parts are treated with a five-stage phosphate bonding process and finished with high reflectance baked enamel.
- Diffuser is secured continuously along luminaire sides.
- Diffusion wrap-around lens for smooth light distribution.
- Performance engineered optical lens assembly delivers unique beam angles and reduces glare.
- High quality LED Chips provide high efficiency, heat dissipation, stability, and lumen maintenance.
- Driver disconnect provided where required to comply with US and Canadian codes.
- Can be surface or pendant (cable, hanging chain or stem kits) mounted.
- Class II/P driver, with 0-10V or Triac dimming
- Ambient Temperature:-30 ~ 40 °C(-22° F to +104° F)
- Damp Location Rated

APPLICATIONS:

Storage rooms/Offices
Conference rooms/Retail
Reception areas/Hallways
Education facilities
Parking Garages



ORDERING: (KK=CCT, can be 30, 35, 40, 50)

Item	Watts	Efficacy	Lumens	CRI	Dimension(L*W*H):Inch		
WR456ELM02012BKKW	20W	130lm/w	2,600lm	>82	23 2/4" 597mm	4 6/8" 120mm	3 5/8" 92mm
WR456ELM04014BKKW	40W	130lm/w	5,200lm	>82	46 5/8" 1184mm	4 6/8" 120mm	3 5/8" 92mm
WR456ELM05014BKKW	50W	130lm/w	6,500lm	>82	46 5/8" 1184mm	4 6/8" 120mm	3 5/8" 92mm

*Please contact your Brandon representative to order products that don't have order codes listed.

*Due to continuing product improvements, Brandon Lighting reserves the right to change the specifications without notice.



OPTIONS:

Order Code

AC347-480V High Voltage	347V
Occupancy Sensor	OS
Daylight Harvesting	DH
Emergency Backup	EM
CCT 3000K,3500K,4000K,5000K	30/35/40/50
Suspension Chain	SC
Clear lens	CL

